

The discreet Atmospherix AS performs remarkably for in ceiling stereo music listening and providing high quality background music for multiple rooms.

With speaker components mounted directly on the front baffle, the Atmospherix AS delivers a true high fidelity performance, and maintains accurate and controlled bass performance from the discreet in ceiling mounted enclosure.

Part of the Krix Architectural Series, the Atmospherix AS is tonally balanced to the Krix floorstanding and bookshelf speaker ranges, making it an ideal speaker system for matching with a Krix home theatre. A large 130mm bass driver with large magnet and copper shorting ring delivers bass and midrange clarity, while a 26mm ring radiator provides extended high frequency performance.

The moving components of the Atmospherix AS are protected from dust and debris through a fully-enclosed back box, designed to optimise the performance from the bass driver, allowing maximum controlled bass and consistency while drastically reducing sound leakage to other rooms. The attractively-styled, slim bezel grille is made from rust resistant stainless steel and snaps into place with magnets, making installation easy. Being paintable, these speakers will involve you in their sound, while disappearing to be heard, but not seen.

For the ultimate sound experience at home, play it through Krix.

FEATURES

- High fidelity bookshelf-speaker sound in your ceiling
- Even dispersion throughout your room
- Fully-enclosed back box



Atmospherix AS	
Frequency Range	45Hz - 40kHz (in room response)
Power Handling	20 - 120 Watts RMS recommended amplifier power
Sensitivity	90 dB (2.83V / 1m)
Impedance	Nominal 6 Ohms (Minimum 3.9 Ohms)
Configuration	2-Way
Low Frequency Driver	Cast aluminium basket with a nominal 130mm (5") doped curvilinear paper cone. 25mm (1") voice coil wound on high powered aluminium former with copper shorting ring. Vented and double magnet shielded
High Frequency Driver	26mm (1") ring radiator tweeter
Enclosure Type	Bass reflex, front vented
Input Terminals	Gold plated spring terminals
Dimensions	295mm diameter x 183mm mounting depth
Cut Out Diameter	247mm diameter recommended
Net Weight	2.5 kg

DETAILED DIMENSIONS

